

Forklift Seat Belt

Seat Belt for Forklift - Explained in the Regulation guidelines are the utilization of operative restraints and seatbelts on forklifts. It says that the responsibility falls on the employers' to ensure that each machinery, piece of equipment and device is used properly used in accordance to the directions of the manufacturer.

In regards to their design, maintenance, inspection, fabrication and use Rough Terrain lift trucks have to meet the regulations of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile equipment along with a Rollover Protective Structure, or ROPS for short, must include seat belts that satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machine has seat belts required by law, the operator and subsequent passengers need to ensure they utilize the belts each time the vehicle is in motion or engaged in operation since this can cause the machine to become unstable and hence, unsafe.

If a seat belt or various driver restraint is needed on a forklift.

While working a lift truck, the seat belt requirements will depend on several factors. Contributing factors to this determination might include whether the the forklift is equipped along with a Rollover Protective Structure, the type of lift truck itself and the year the forklift was actually made. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial forklifts, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, system, or enclosure. A driver restraint device, enclosure or system is designed so as to assist the driver in reducing the danger of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The restraint device or system can consist of a seat belt, even though a seat belt is not essentially a part of such machine or system.